



适用电线 AWG#(mm <sup>2</sup> )	螺栓孔尺寸		零件号		标准	尺寸mm (in.)								工具型号	数量/箱	
	美制	米制	JST	JIS		$\phi d_2$	B	L	F	E	$\phi D$	$\phi d_1$	T			
16~14 (1.04~2.63)	3/8	9	2-9		UL SP	9.8 (.386)	13.6 (.535)	25.5(1.004)	13.9 (.547)	4.8 (.189)	4.1 (.161)	2.3 (.091)	0.8 (.031)	YHT-2210 YA-1 YA-2 YA-4 BCT-0514L	1,000	
	3/8	10	2-10			10.5 (.413)	13.6 (.535)	25.5(1.004)	13.9 (.547)							
	1/2	12	2-12			13.0 (.512)	19.0 (.748)	31.0(1.220)	16.7 (.675)						500	
	1/2	14	2-14			15.0 (.591)	27.0(1.063)	39.5(1.555)	21.2 (.835)							
	5/8	16	2-16			17.0 (.669)	27.0(1.063)	39.5(1.555)	21.2 (.835)							
	3/4	20	2-20			21.0 (.827)	27.0(1.063)	39.5(1.555)	21.2 (.835)							
14~12 (3.5)	3-4	3	3.5-R3		UL SP	3.2 (.126)	8.0 (.315)	17.8 (.707)	9.0 (.354)	4.8 (.189)	4.8 (.189)	2.7 (.106)	1.0 (.039)	YHT-2210 (5号刀刃) BCT-0514L	1,000	
	8	4	3.5-R4			4.3 (.169)	8.0 (.315)	17.8 (.707)	9.0 (.354)							
	8	4	3.5-4			4.3 (.169)	10.3 (.406)	18.6 (.732)	8.6 (.339)							
	10	5	3.5-R5			5.3 (.209)	8.0 (.315)	17.8 (.707)	9.0 (.354)							
	10	5	3.5-5			5.3 (.209)	10.3 (.406)	18.6 (.732)	8.6 (.339)							
	1/4	6	3.5-6			6.4 (.252)	10.3 (.406)	18.6 (.732)	8.6 (.339)							
12~10 (2.63~6.64)	3-4	3	5.5-S3.3		UL SP	3.2 (.126)	7.2 (.283)	15.7 (.618)	5.9 (.232)	6.8 (.268)	5.6 (.220)	3.4 (.134)	1.0 (.039)	YHT-2210 YA-1 YA-2 YA-4 BCT-0514L	500	
	3-4	3	5.5-3			3.2 (.126)	9.5 (.374)	19.8 (.780)	8.3 (.327)							6.8 (.268)
	5-6	3.5	5.5-S3			3.7 (.146)	7.2 (.283)	15.7 (.618)	5.9 (.232)							6.2 (.244)
	5-6	3.5	5.5-3.7			3.7 (.146)	9.5 (.374)	19.8 (.780)	8.3 (.327)							6.8 (.268)
	8	4	5.5-S4			4.3 (.169)	7.2 (.283)	15.7 (.618)	5.9 (.232)							6.2 (.244)
	8	4	5.5-4NS		UL SP JIS	4.3 (.169)	8.0 (.315)	19.1 (.752)	8.3 (.327)						1,000	
	8	4	5.5-4	R5.5-4		4.3 (.169)	9.5 (.374)	19.8 (.780)	8.3 (.327)							500
	10	5	5.5-5NS		UL SP JIS	5.3 (.209)	8.0 (.315)	19.1 (.752)	8.3 (.327)						1,000	
	10	5	5.5-5	R5.5-5		5.3 (.209)	9.5 (.374)	19.8 (.780)	8.3 (.327)						500	
	10	5	5.5-S5		UL SP	5.3 (.209)	13.2 (.520)	22.4 (.882)	9.0 (.354)						1,000	
	1/4	6	5.5-6NS			6.4 (.252)	9.0 (.354)	24.3 (.957)	13.0 (.512)							500
	1/4	6	5.5-6	R5.5-6	UL SP JIS	6.4 (.252)	12.0 (.472)	25.8(1.016)	13.0 (.512)						1,000	
	1/4	6	5.5-S6			6.4 (.252)	13.2 (.520)	22.4 (.882)	9.0 (.354)							500
	1/4	6	5.5-L6		UL SP	6.4 (.252)	15.0 (.591)	28.0(1.102)	13.7 (.539)						500	
	5/16	8	5.5-S8			8.4 (.331)	13.2 (.520)	22.4 (.882)	9.0 (.354)							
	5/16	8	5.5-8	R5.5-8	UL SP JIS	8.4 (.331)	15.0 (.591)	28.0(1.102)	13.7 (.539)						500	
	3/8	9	5.5-9			9.8 (.386)	15.0 (.591)	28.0(1.102)	13.7 (.539)							
	3/8	10	5.5-10	R5.5-10	UL SP JIS	10.5 (.413)	15.0 (.591)	28.0(1.102)	13.7 (.539)						200	
	1/2	12	5.5-12			13.0 (.512)	19.2 (.756)	32.4(1.276)	16.0 (.630)							
	1/2	14	5.5-14		UL SP	15.0 (.591)	32.0(1.260)	48.1(1.894)	25.3 (.996)							
5/8	16	5.5-16		17.0 (.669)		32.0(1.260)	48.1(1.894)	25.3 (.996)								
11/16	18	5.5-18		19.0 (.748)		32.0(1.260)	48.1(1.894)	25.3 (.996)								
3/4	20	5.5-20		21.0 (.827)		32.0(1.260)	48.1(1.894)	25.3 (.996)								

注：1) 标有JIS标志 ㊤ 的产品符合JIS C2805标准。

2) 上表所示的零件号对应带焊接缝的产品。

订购带对接焊接缝的产品（公称尺寸：0.5~5.5）时，应在零件号前面加上前缀“WS”（如5.5-4->WS5.5-4）。

3) 生产交货周期因产品类型而异。详情请垂询本公司。